



1-800-837-7477  
www.atkinsandpearce.com

# NOMEX<sup>®</sup> A-A-52084

Flat braid manufactured from continuous filament Nomex yarn. Formerly known as MIL-T-43435 Type V.

## Features

- ▶ Temperature range: -67°F to 500°F (-55°C to 260°C).
- ▶ See table below for finishes available.
- ▶ Other colors available upon request.



## Sizes Available

Mil-Spec Size	Min. Break Strength (lbs)	Width (in)		Thickness (in)		Spool Size (yds)	Stock Color
		(min)	(max)	(min)	(max)		
1	85	0.180	0.220	0.013	0.019	250 yd.	Natural
2	50	0.099	0.121	0.011	0.017	250 yd.	Natural
3	35	0.068	0.083	0.009	0.015	500 yd.	Natural
4	25	0.050	0.061	0.007	0.013	500 yd.	Natural

Our mil-spec lacing tapes and cords are available with your choice of finish designation.

## Sizes Available

Finish Designation	Finish
A	No Finish
B	Microcrystalline, Fungicidal Wax
C	Synthetic Rubber or Elastomer
D	Teflon
E	Vinyl
F	Silicone Resin
G	Liquid Nylon
*	Self-Extinguishing

\* Meets requirements of finish designation C